



## Technical Data Sheet

B-00331-2	14V VOLTAGE REGULATOR
Duty Voltage Factory Set To Voltage Adjust Range Load Current Weight Dimensions	Continuous Linear 14.0V 13.0V – 15.0V 3.5A Max. 0.3lb. Max. 31/2"L x 31/8"W x 13/4"H
PINOUT	FUNCTION
Red Black Yellow	14V Supply Ground Field Output
OPERATION NOTES	DESCRIPTION
Note 1:  Note 2:	This unit shall be mounted on a metallic surface in the aircraft using 2 #10 screw pulled up tight. Maintain a good thermal conduction path to the airframe.  Provide positive ground connection to aircraft structure.
PART NUMBER	AIRCRAFT ELIGIBILITY
<b>B-00331-2</b> 484-121 B-00267-2 B-00331-1 B-00331-3	<b>Piper</b> PA-24, PA-24-250, PA-24-260, PA-24-400, PA-28-140, PA-28-150, PA-28-151, PA-28-160, PA-28-161, PA-28-180, PA-28-181, PA-28-201T, PA-28-235, PA-28-236, PA-28R-180, PA-28R-200, PA-28R-201, PA-28R-201T, PA-28RT-201, PA-28RT-201T, PA-28S-160, PA-28S-180, PA-32-260, PA-32-300, PA-32-301, PA-32-301FT, PA-32-301T, PA-32-301XTC, PA-32R-300, PA-32R-301(HP), PA-32R-301(SP), PA-32R-301T, PA-32RT-300, PA-32RT-300T, PA-32S-300, PA-38-112, <b>American Champion</b> 11AC, S11AC, 11BC, S11BC, 7AC, 7ACA, S7AC, 7BCM, 7CCM, S7CCM, 7DC, S7DC, 7EC, S7EC, 7ECA, 7FC, 7GC, 7GCA, 7GCAA, 7GCB, 7GCBA, 7HC, 7JC, 7KC, 7KCAB, 8KCAB, 8GCBC, <b>Hawker Beechcraft</b> 19A, B19, M19A, 23, A23, A23A, A23-19, A23-24, B23, C23, A24, A24R, B24R, C24R, <b>CPAC(Commander)</b> 112, 112B, 112TC, 112TCA, 114, 114A, 114B, 114TC, <b>True Flight Holdings(Grumman)</b> AA-1, AA-1A, AA-1B, AA-1C, AA-5, AA-5A, AA-5B, AG-5B, <b>Enstrom</b> F-28, F28A, F-28C, F-28C-2, F-29C-2R, F-28F, F-28F-R, 280, 280C, 280F, 280FX, 480, 380B, TH-28

**NOTE:** Installer must cross-check eligibility with applicable technical data.

Data Sheet B-00331-2.A