



Technical Data Sheet

B-00375-2	28V LOW VOLTAGE MONITOR
Input Voltage Transient Protection Electrical Load Internal Voltage Drop Function Weight Dimensions	16V – 35V Withstand 60V Spikes per MIL-STD-704 Incandescent, equal to 5 MAZDA #327 bulbs (0.2A Max.) 1.5V Max. With Voltage Reduction, lamp turn on at 25V ±0.3V With Voltage Increase, lamp turn off between turn on point and 26V DC 0.08 lb. Max. 1.36"L x 2.38"W x 0.84"H
PINOUT	FUNCTION
Red Black Green	Bus Ground Indicator Bulb, low side
OPERATION NOTES	DESCRIPTION
Note 1: Note 2: Note 3:	CAUTION: Shorted load will result in immediate permanent damage. This unit is potted for durability and can not be repaired. Dimensions are reference only.
PART NUMBER	AIRCRAFT ELIGIBILITY
B-00375-2 475-272	Piper PA-31, PA-31-300, PA-31-325, PA-31-350, PA-31P, PA-31P-350, PA-31T, PA-31T1, PA-31T2, PA-31T3, PA-34-200, PA-34-200T, PA-34-220T, PA-46-310P, PA-46-350P, PA-46-500TP, PA-46R-350T

NOTE: Installer must cross-check eligibility with applicable technical data.

Data Sheet B-00375-2.A